



**CASUMINA**  
THE TRUE COMPANION

# GS851



## SPECIFICATIONS

- **Small block - rib pattern design with staggered blocks**

Good driving  
Comfortable and steady drive  
Good grip while turning corners

- **Multiple sinuous sipes all over tread**

Good heat dissipation and well drainage  
Good traction on wet roads

- **Linked blocks at shoulders**

Reduce irregular wear and block damages  
Increase durability and lifetime

SIZE	295/80R22.5
PR	18
TYPE	TL
LOAD INDEX	154/149
SPEED RATING	M
MAX. SINGLE	3750 kg
MAX. DUAL	3250 kg
WIDTH	292 mm
O. DIAMETER	1046 mm
TREAD DEPTH	19 mm
WEIGHT	63 kg



# GS611

## SPECIFICATIONS

- **Rib pattern design**

Good driving  
Fuel saving  
Comfortable drive and low noise

- **Wide grooves with multiple sipes stone rejection platform**

Good heat dissipation  
Avoid stone capture

- **Large tread and seamless shoulders**

Reduce irregular wear  
Improve durability and lifetime

SIZE	295/80R22.5
PR	18
TYPE	TL
LOAD INDEX	154/149
SPEED RATING	M
MAX. SINGLE	3750 kg
MAX. DUAL	3250 kg
WIDTH	301 mm
O. DIAMETER	1048 mm
TREAD DEPTH	15 mm
WEIGHT	57.9 kg



# GS625



## SPECIFICATIONS

- Rib pattern design, with three equal ribs in the middle

Good driving  
Fuel saving

- Staggered jagged grooves with multiple sipes and stone rejection platform

Good heat dissipation  
Avoidable stone captured

- Large footprint and seamless shoulders

Low noise and good traction  
Reduce irregular wear  
Increase durability and lifetime

SIZE	275/80R22.5
PR	16
TYPE	TL
LOAD INDEX	149/146
SPEED RATING	M
MAX. SINGLE	3250 kg
MAX. DUAL	3000 kg
WIDTH	278.7 mm
O. DIAMETER	1010 mm
TREAD DEPTH	14.35 mm
WEIGHT	54 kg



# BS611



## SPECIFICATIONS

- Rib-block mixed pattern design

High load capacity, anti slippage  
Comfortable drive and low noise  
Fuel saving

- Wide and deep grooves form big blocks in the middle

Good traction  
Good heat dissipation and well drainage

- Large tread and seamless shoulders

Reduce irregular wear  
Increase durability and lifetime

SIZE	275/80R22.5
PR	16
TYPE	TL
LOAD INDEX	149/146
SPEED RATING	M
MAX. SINGLE	3250
MAX. DUAL	3000
WIDTH	273 mm
O. DIAMETER	1012 mm
TREAD DEPTH	17 mm
WEIGHT	55.2 kg

